

View Online at <https://aerobasegroup.com/nsn/5930-00-997-8197>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

Between 0.944 inches and 1.006 inches

Body Length:

1.100 inches

Body Width:

Between 0.875 inches and 0.937 inches

Body Height:

Between 0.469 inches and 0.531 inches

Case Material:

Plastic

Actuator Style:

Roller plunger

Actuator Roller Diameter:

Between 0.307 inches and 0.317 inches

Actuator Roller Width:

Between 0.068 inches and 0.076 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.438 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

16.0 ounces

Switch Actuating Force:

96.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.125 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes lamp dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0