NSN 5930-00-997-8357

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-997-8357

Body Style:
Hole mounted
Overall Length:
1.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
0.879 inches
Overall Width:
0.283 inches
Body Length:
1.200 inches
Body Width:
0.283 inches
Body Height:
0.820 inches
Unthreaded Mounting Hole Diameter:
0.094 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.625 inches
Actuator Style:
Round
Actuator Diameter:
0.093 inches
Actuator Height:
0.059 inches
Actuator Free Position Height:
0.171 inches
Maximum Voltage Rating In Volts:
125.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
3.0 ounces
Switch Actuating Force:

Actuator Movement:

Between 10.0 ounces and 16.0 ounces

Between 0.051 pretravel inches and 0.025 overtravel inches and 0.025 differential inches

NSN 5930-00-997-8357

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage	Contact Load	Current Rating	At Maximum	Rated	Voltage
--	--------------	-----------------------	------------	-------	---------

3.000 amperes resistive dc and 7.500 amperes resistive ac

Precious Material And Location:

Contact surfaces gold

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

Unit Of Measure:

--

N/a

Demilitarization:

No

Fiig:

A053a0