

View Online at <https://aerobasegroup.com/nsn/5930-00-998-5568>

**Thread Length:**

0.500 inches single pressure connection

**Hazardous Locations/environmental Protection:**

Driptight

**Overall Length:**

1.880 inches

**Outside Diameter:**

0.375 inches single connection

**Body Length:**

0.680 inches

**Overall Diameter:**

1.680 inches

**End Application:**

Hh-60h search and rescue, sh-60f carrier-based, ah-1w advance attack, hh-60j uscg search and rescue helicopters. P12 fire/crash truck. C-2a repro cured aircraft. Mb-4 aircraft towing tractor. Shipboard material handling (mhe). B-2 bomber (se) support equipment.

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Mounting Method:**

Inlet connection

**Thready Qty Per Inch (tpi):**

27 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

150.00 pounds per square inch

**Thread Size:**

0.125 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Criticality Code Justification:**

Feat

**Sensing Element Burst Pressure:**

450.00 pounds per square inch

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point not adjustable

**Contact Stimulus Rating:**

15.00 actuation point pounds per square inch

**Contact Voltage Rating In Volts:**

6.0 dc at sea level single voltage

**Pressure Connector Type:**

Plain, threaded external single connection

**Special Features:**

Weapon system essential

**Media For Which Designed:**

Liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0