

View Online at <https://aerobasegroup.com/nsn/5930-00-998-5568>

Thread Length:

0.500 inches single pressure connection

Hazardous Locations/environmental Protection:

Driptight

Overall Length:

1.880 inches

Outside Diameter:

0.375 inches single connection

Body Length:

0.680 inches

Overall Diameter:

1.680 inches

End Application:

Hh-60h search and rescue, sh-60f carrier-based, ah-1w advance attack, hh-60j uscg search and rescue helicopters. P12 fire/crash truck. C-2a repro cured aircraft. Mb-4 aircraft towing tractor. Shipboard material handling (mhe). B-2 bomber (se) support equipment.

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit

Mounting Method:

Inlet connection

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Criticality Code Justification:

Feat

Sensing Element Burst Pressure:

450.00 pounds per square inch

Terminal Type:

Tab w/screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

15.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

6.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Special Features:

Weapon system essential

Media For Which Designed:

Liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0