

View Online at <https://aerobasegroup.com/nsn/5930-00-998-6908>

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

1.937 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

Between 1.922 inches and 1.952 inches

**Body Width:**

Between 0.672 inches and 0.702 inches

**Body Height:**

0.984 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Style:**

Round

**Actuator Free Position Height:**

Between 1.035 inches and 1.085 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

28.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.050 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.000 amperes inductive dc and 1.500 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 1.500 amperes lamp ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0