

View Online at <https://aerobasegroup.com/nsn/5930-00-998-6908>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.937 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

Between 1.922 inches and 1.952 inches

Body Width:

Between 0.672 inches and 0.702 inches

Body Height:

0.984 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Free Position Height:

Between 1.035 inches and 1.085 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

28.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.050 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 1.500 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 1.500 amperes lamp ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0