NSN 5930-00-998-6910

Sensitive Switch - Page 1 of 2

3 screw



View Online at https://aerobasegroup.com/nsn/5930-00-998-6910

view Online at https://aerobasegroup.com/nsn/5930-00-998-6910
Body Style:
Hole mounted
Overall Length:
1.937 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
Between 1.922 inches and 1.952 inches
Body Width:
Between 0.672 inches and 0.702 inches
Body Height:
0.984 inches
Unthreaded Mounting Hole Diameter:
0.139 inches
Actuator Length:
2.469 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.125 inches
Actuator Roller Diameter:
0.375 inches
Actuator Roller Width:
0.150 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
13.0 ounces
Actuator Movement:
Between 0.040 pretravel inches and 0.005 overtravel inches and 0.005 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
2.000 amperes resistive dc and 1.000 amperes inductive dc and 1.500 amperes lamp dc and 15.000 amperes resistive ac and 15.000
amperes inductive ac and 1.500 amperes lamp ac
Terminal Type And Quantity:

NSN 5930-00-998-6910

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0