

View Online at <https://aerobasegroup.com/nsn/5930-00-998-9233>

**Hazardous Locations/environmental Protection:**

Corrosion resistant and dustproof and vibration resistant and watertight

**Overall Length:**

4.750 inches

**Outside Diameter:**

0.750 inches single connection

**Overall Height:**

5.625 inches

**Overall Width:**

1.960 inches

**Body Height:**

3.500 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Longest Horizontal Distance Between Mounting Centers:**

4.250 inches

**Longest Vertical Distance Between Mounting Centers:**

2.875 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

2500.00 pounds per square inch

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+50.00/+1000.00 actuation point pounds per square inch and +50.00/+1000.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point hex nut and internal deactuation point hex nut

**Contact Voltage Rating In Volts:**

250.0 ac at sea level single voltage

**Pressure Connector Type:**

Shoulder, unthreaded external single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0