

View Online at <https://aerobasegroup.com/nsn/5930-00-999-0160>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

1.585 inches

Overall Height:

Between 0.985 inches and 1.015 inches

Overall Width:

Between 0.922 inches and 0.952 inches

First Flat Length:

0.398 inches single actuator

Flat Height:

0.215 inches single actuator

Shaft Diameter:

0.247 inches single actuator and 0.253 inches single actuator

Shaft Length:

0.710 inches single actuator

Nonturn Device Radius:

0.375 inches at 1:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 1:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

6 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

90.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0