

View Online at <https://aerobasegroup.com/nsn/5930-00-999-0390>

Thread Class:

2a single mounting facility

Thread Length:

0.430 inches single mounting facility

Width Between Flats:

0.050 inches 2nd actuator

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.220 inches

First Flat Length:

0.060 inches 2nd actuator

Flat Height:

0.230 inches 1st actuator and 0.235 inches 1st actuator

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.590 inches 2nd actuator

Overall Diameter:

1.150 inches

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

6 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Pull to turn

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

60.0 degrees from nonturn device 2nd actuator

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, parallel flatted, threaded hole 2nd actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0