

View Online at <https://aerobasegroup.com/nsn/5930-00-999-4401>

**Body Style:**

Bushing mounted

**Overall Length:**

0.850 inches

**Overall Height:**

1.650 inches

**Overall Width:**

0.656 inches

**Bushing Length:**

Between 0.290 inches and 0.330 inches

**Body Length:**

0.850 inches

**Body Width:**

0.656 inches

**Body Height:**

1.110 inches

**Actuator Diameter:**

Between 0.318 inches and 0.338 inches

**Actuator Height:**

Between 0.180 inches and 0.220 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Test Data Document:**

81349-mil-prf-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 turret

**Specification Data:**

81349-mil-prf-8805/23 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0

**Mil-std (military Standard):**

Mil-prf-8805 spec.