

View Online at <https://aerobasegroup.com/nsn/5930-00-999-4753>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

Between 0.771 inches and 0.791 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.346 inches and 0.366 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Style:

Round

Actuator Diameter:

0.092 inches

Actuator Height:

0.090 inches

Actuator Free Position Height:

0.366 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0