## NSN 5930-00-999-4885

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-999-4885

**Thread Class:** 

3a single threaded bushing

**Overall Length:** 

2.438 inches

**Body Diameter:** 

0.312 inches

**Body Length:** 

1.407 inches

**Tempurature Sensing Element Type:** 

Internal sensor

Width Across Flats:

0.875 inches

**Operating Tempurature Rating:** 

Between -70.0 degrees fahrenheit and 800.0 degrees fahrenheit

**Mounting Method:** 

Threaded bushing

**Features Provided:** 

Electrical access port

Thready Qty Per Inch (tpi):

20 single threaded bushing

**Contact Action Stimulus:** 

Increase

**Thread Size:** 

0.500 inches single threaded bushing

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, normally open, momentary action

**Terminal Type:** 

Connector, receptacle

**Contact Load Current Rating:** 

2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage

**Contact Adjustability:** 

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:** 

-20.00/+600.00 actuation point degrees fahrenheit and -20.00/+600.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:** 

External deactuation point knob and external actuation point knob

**Contact Stimulus Rating:** 

250.00 actuation point degrees fahrenheit and 250.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level second voltage

Media For Which Designed:

Gas

## NSN 5930-00-999-4885

Thermostatic Switch - Page 2 of 2



| Style | De | sia | nato | r: |
|-------|----|-----|------|----|
|       | -  | 9.9 | ···  |    |

Cylindrical w/flange

## **Thread Series Designator:**

Unf single threaded bushing

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0