## NSN 5930-01-003-3422

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-003-3422

Body Style:
Panel mounted
Overall Length:
2.950 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Length:
0.688 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.220 inches and 0.240 inches
Actuator Width:
0.620 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.720 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac and 7.500 amperes resistive dc and 5.000 amperes
inductive dc and 1.000 amperes lamp dc
Precious Material And Location:
Contacts silver and contact surfaces gold
Unable To Decode:
Unable to decode and unable to decode

14 socket, integrated wire termination

**Terminal Type And Quantity:** 

## NSN 5930-01-003-3422

Push Switch - Page 2 of 2



_			-		
C	hο	14		.ife	•
•			_	.II C	-

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0