## NSN 5930-01-004-9902

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-004-9902 **Overall Length:** Between 1.190 inches and 1.260 inches **Overall Height:** 0.607 inches **Body Diameter:** 0.572 inches **Body Height:** 0.315 inches **Distance Between Mounting Facility Centers:** 0.937 inches **Tempurature Sensing Element Type:** Internal sensor **Mounting Method: Bracket Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 1 pole, single throw, both positions maintained **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 160.00 actuation point degrees fahrenheit and 145.00 deactuation point degrees fahrenheit **Contact Voltage Rating In Volts:** 28.0 dc at sea level second voltage Frequency In Hertz: 60.0 first voltage Media For Which Designed: Gas or liquid **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Style Designator:** 

N/a

Disc w/flange Shelf Life:

## NSN 5930-01-004-9902

Thermostatic Switch - Page 2 of 2



|    | • • |             |     |     |      |
|----|-----|-------------|-----|-----|------|
| In | 18  | <i>(</i> )+ | МЛО | 201 | ure: |
|    |     |             |     |     |      |

--

Demilitarization:

No

Fiig:

A048b0