## NSN 5930-01-005-2644

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-005-2644

**Thread Class:** 2b single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 2.875 inches **Overall Height:** 2.500 inches **Overall Width:** 2.500 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.125 inches single actuator **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.641 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 1.641 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 125.0 ac at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round, hollowed single actuator **Terminal Type:** Screw **Switch Actuator Positioning Increment:** 

90.0 degrees single actuator

## NSN 5930-01-005-2644

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

10.0 amperes resistive load ac at sea level

**Style Designator:** 

Tap, circuit selector

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A052b0