

View Online at <https://aerobasegroup.com/nsn/5930-01-005-2647>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Bushing Length:

0.812 inches

Body Length:

1.467 inches

Body Width:

2.550 inches

Body Height:

1.050 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

Between 0.751 inches and 0.810 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.120 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded bushing

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

32.0 ounces

Switch Actuating Force:

96.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0