

View Online at <https://aerobasegroup.com/nsn/5930-01-005-2647>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Bushing Length:**

0.812 inches

**Body Length:**

1.467 inches

**Body Width:**

2.550 inches

**Body Height:**

1.050 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

Between 0.751 inches and 0.810 inches

**Actuator Roller Diameter:**

0.500 inches

**Actuator Roller Width:**

0.120 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded bushing

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

32.0 ounces

**Switch Actuating Force:**

96.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0