

View Online at <https://aerobasegroup.com/nsn/5930-01-005-3725>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

5.266 inches

Body Diameter:

0.625 inches

Body Length:

3.703 inches

Overall Diameter:

3.750 inches

Unthreaded Mounting Hole Diameter:

0.169 inches

Distance Between Mounting Facility Centers:

1.731 inches

Temperature Sensing Element Type:

Immersion well

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

500.0 milliamperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+100.00/+300.00 actuation point degrees fahrenheit and +100.00/+300.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

200.00 actuation point degrees fahrenheit and 197.50 deactuation point degrees fahrenheit and 2.50 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

250.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0