NSN 5930-01-005-6474

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-005-6474

| Hazardous Locations/environmental Protection: |
|---|
| Explosion proof |
| Overall Length: |
| 6.188 inches |
| Overall Height: |
| 4.750 inches |
| Overall Width: |
| 4.750 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.406 inches single mounting facility and 0.410 inches single mounting facility |
| Individual Section Quantity: |
| 2 |
| Knob Manufacturer Code: |
| 82121 |
| Knob Manufacturer Part Number: |
| A |
| Longest Horizontal Distance Between Mounting Centers: |
| 3.781 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 3.781 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section front |
| Throw Quantity: |
| 1 each section front |
| Mounting Method: |
| Bracket single mounting facility and unthreaded hole single mounting facility |
| Features Provided: |
| Actuator knob |
| Contact Voltage Rating In Volts: |
| 500.0 ac at sea level |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 2 single actuator |
| Criticality Code Justification: |
| Feat |
| Terminal Type: |
| Tab, solder lug |
| Contact Switching Action: |

Breaks before makes each section front

NSN 5930-01-005-6474

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

60.0 amperes resistive load ac at sea level

Special Features:

Item must comply with rqmt of desc production standard no. L01785

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0