

View Online at <https://aerobasegroup.com/nsn/5930-01-005-6474>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

6.188 inches

**Overall Height:**

4.750 inches

**Overall Width:**

4.750 inches

**Unthreaded Mounting Hole Diameter:**

0.406 inches single mounting facility and 0.410 inches single mounting facility

**Individual Section Quantity:**

2

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

A

**Longest Horizontal Distance Between Mounting Centers:**

3.781 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

3.781 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

1 each section front

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

500.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

60.0 amperes resistive load ac at sea level

**Special Features:**

Item must comply with rqmt of desc production standard no. L01785

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0