NSN 5930-01-005-6482

Sensitive Switch - Page 1 of 2

Body Style:

Bushing mounted



View Online at https://aerobasegroup.com/nsn/5930-01-005-6482

| Hazardous Locations/environmental Protection: |
|--|
| Weatherproof |
| Body Diameter: |
| 1.000 inches |
| Bushing Length: |
| 1.640 inches |
| Body Length: |
| 0.980 inches |
| Case Material: |
| Metal |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.250 inches |
| Actuator Height: |
| 0.622 inches |
| Actuator Free Position Height: |
| 0.652 inches |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thread Size: |
| 0.625 inches |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 64.0 ounces |
| Switch Actuating Force: |
| 192.0 ounces |
| Actuator Movement: |
| 0.040 pretravel inches and 0.500 overtravel inches and 0.020 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 1.000 amperes inductive dc and 4.000 amperes motor dc |
| Thread Series Designator: |
| Unef |
| Terminal Type And Quantity: |
| 6 wire lead |
| |

NSN 5930-01-005-6482

Sensitive Switch - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0