NSN 5930-01-005-6482

Sensitive Switch - Page 1 of 2

Body Style:

Bushing mounted



View Online at https://aerobasegroup.com/nsn/5930-01-005-6482

Hazardous Locations/environmental Protection:
Weatherproof
Body Diameter:
1.000 inches
Bushing Length:
1.640 inches
Body Length:
0.980 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.622 inches
Actuator Free Position Height:
0.652 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
64.0 ounces
Switch Actuating Force:
192.0 ounces
Actuator Movement:
0.040 pretravel inches and 0.500 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 1.000 amperes inductive dc and 4.000 amperes motor dc
Thread Series Designator:
Unef
Terminal Type And Quantity:
6 wire lead

NSN 5930-01-005-6482

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0