## NSN 5930-01-005-9447

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-005-9447
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
5.032 inches
Overall Height:
2.812 inches
Overall Width:
2.812 inches
Individual Section Quantity:
3
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
G
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Facility Circle Radius:
1.625 inches single mounting facility
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
30.0 dc at sea level
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator
Criticality Code Justification:
Zzzy

**Square Shaft Size:** 

0.250 inches single actuator

## **NSN 5930-01-005-9447**Rotary Switch - Page 2 of 2



Terminal Type:
Tab w/screw
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load dc at sea level
Special Features:
tem must comply with requirements of defense supply center columbus production standard no. Loxxxx
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Reference Number Differentiating Characteristics:
Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing
and testing specifications available at the dla icp
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A052b0