

View Online at <https://aerobasegroup.com/nsn/5930-01-005-9447>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

5.032 inches

**Overall Height:**

2.812 inches

**Overall Width:**

2.812 inches

**Individual Section Quantity:**

3

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

G

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:**

1.625 inches single mounting facility

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Mounting Facility Pattern:**

Four position circular single mounting facility

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Rectangular/square, threaded hole single actuator

**Criticality Code Justification:**

Zzzy

**Square Shaft Size:**

0.250 inches single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load dc at sea level

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard no. Lxxxxx

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc single mounting facility

**Reference Number Differentiating Characteristics:**

Arefernce number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0