

View Online at <https://aerobasegroup.com/nsn/5930-01-005-9447>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.032 inches

Overall Height:

2.812 inches

Overall Width:

2.812 inches

Individual Section Quantity:

3

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

G

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.625 inches single mounting facility

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Criticality Code Justification:

Zzzy

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

Special Features:

Item must comply with requirements of defense supply center columbus production standard no. Lxxxx

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0