NSN 5930-01-006-7831

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-006-7831

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Fungus resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

Between 0.677 inches and 0.697 inches

Body Height:

Between 0.806 inches and 0.846 inches

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.142 inches

Actuator Length:

Between 1.860 inches and 1.890 inches

Actuator Style:

Leaf

Actuator Width:

0.190 inches

Actuator Free Position Height:

Between 0.954 inches and 1.014 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.75 ounces

Switch Actuating Force:

3.5 ounces

Actuator Movement:

Between 0.234 pretravel inches and 0.156 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

NSN 5930-01-006-7831

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

