NSN 5930-01-006-8265

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-006-8265

Hazardous Locations/environmental Protection:				
Explosion proof				
Overall Length:				
7.250 inches				
Overall Height:				
2.906 inches				
Overall Width:				
2.812 inches				
Unthreaded Mounting Hole Diameter:				
0.221 inches single mounting facility				
Individual Section Quantity:				
5				
Knob Manufacturer Code:				
82121				
Knob Manufacturer Part Number:				
G				
Longest Horizontal Distance Between Mounting Centers:				
2.000 inches single mounting facility				
Shortest Horizontal Distance Between Mounting Centers:				
1.000 inches single mounting facility				
Longest Vertical Distance Between Mounting Centers:				
2.188 inches single mounting facility				
Switch Contact Basic Design:				
Nonpile-up nonsymmetrical				
Mounting Method:				
Unthreaded hole single mounting facility				
Features Provided:				
Actuator knob				
Contact Voltage Rating In Volts:				
500.0 highest ac voltage rating at sea level				
Mounting Facility Pattern:				
Isosceles triangle single mounting facility				
Switch Actuator Indexing Position Quantity:				
4 single actuator				
Shaft Type:				
Rectangular/square, threaded hole single actuator				
Square Shaft Size:				
0.375 inches single actuator				
Terminal Type:				
Tab w/screw				
Switch Actuator Positioning Increment:				

90.0 degrees single actuator

NSN 5930-01-006-8265

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

5.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0