

View Online at <https://aerobasegroup.com/nsn/5930-01-006-8267>

Body Style:

Bushing mount

Bushing Length:

0.470 inches

Body Length:

0.575 inches

Body Width:

0.535 inches

Body Height:

0.640 inches

Actuator Style:

Round

Actuator Diameter:

0.425 inches

Actuator Height:

1.105 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0