

View Online at <https://aerobasegroup.com/nsn/5930-01-006-8808>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Humidity resistant and salt spray resistant and shock resistant and vibration resistant

Overall Length:

1.700 inches

Overall Height:

1.692 inches

Overall Width:

1.366 inches

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.178 inches single mounting facility

Operating Temperature Range:

-65.0/+100.0 degrees celsius

Mounting Method:

Flange single mounting facility and threaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Thready Qty Per Inch (tpi):

56 single mounting facility

Thread Size:

0.086 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Eight position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

10 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section

Contact Arrangement Truth Table:

Bcd with complement, 1 pole - 10 positions each section

Color:

White each indicator marking

Precious Material And Location:

Stator surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0