

View Online at <https://aerobasegroup.com/nsn/5930-01-006-9669>

Body Style:

Bushing mount

Bushing Length:

Between 0.335 inches and 0.365 inches

Body Length:

Between 0.490 inches and 0.505 inches

Body Width:

Between 0.265 inches and 0.275 inches

Body Height:

Between 0.342 inches and 0.358 inches

Actuator Style:

Round

Actuator Diameter:

0.115 inches

Actuator Height:

Between 0.395 inches and 0.425 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0