NSN 5930-01-007-0545

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-007-0545
Thread Class:
3b all pressure connection
Inside Diameter:
0.438 inches all connections
Overall Length:
3.600 inches
Overall Height:
3.600 inches
Body Diameter:
2.400 inches
Unthreaded Mounting Hole Diameter:
0.210 inches
Distance Between Mounting Facility Centers:
3.000 inches
Pressure Switch Type:
Differential
Operating Tempurature Rating:
Between -67.0 degrees fahrenheit and 160.0 degrees fahrenheit
Mounting Method:
Flange and unthreaded hole
Contact Action Stimulus:
Increase
Proof Pressure:
180.00 pounds per square inch
Thread Size:
0.438 inches all pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Sensing Element Burst Pressure:

240.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage and 3.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

15.00 actuation point pounds per square inch and 25.00 actuation point pounds per square inch

NSN 5930-01-007-0545

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Gasket seal, threaded internal all connections

Special Features:

Essential to weapon systems performance

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Thread Series Designator:

Unjf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0