

View Online at <https://aerobasegroup.com/nsn/5930-01-007-1730>

**Hazardous Locations/environmental Protection:**

Dustproof and watertight

**Overall Length:**

4.875 inches

**Overall Height:**

5.750 inches

**Overall Width:**

2.812 inches

**Body Height:**

2.500 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.406 inches

**Shortest Horizontal Distance Between Mounting Centers:**

1.750 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

9.6 amperes resistive load fourth voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+9.00/+79.00 actuation point pounds per square inch and +5.00/+75.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

4.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

550.0 dc at sea level third voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiq:**

A048b0