NSN 5930-01-007-1737

Rotary Switch - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5930-01-007-1737

2b single mounting facility **Hazardous Locations/environmental Protection:** Explosion proof **Overall Length:** 6.407 inches **Overall Height:** 2.812 inches **Overall Width:** 2.812 inches **Individual Section Quantity: Operating Tempurature Range:** -65.0/+125.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Facility Circle Radius:** 1.625 inches single mounting facility **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 30.0 dc at sea level **Mounting Facility Pattern:** Four position circular single mounting facility **Switch Actuator Indexing Position Quantity:** 12 single actuator **Terminal Type:** Tab w/screw **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Switch Actuator Stop Device Type:** Adjustable stop single actuator **Contact Load Current Rating:**

Style Designator:Tap, circuit selector

7.5 amperes resistive load ac at sea level

NSN 5930-01-007-1737

Rotary Switch - Page 2 of 2



T	hre	ead	Series	Desig	ınator
-			-0	- 00.9	

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0