# NSN 5930-01-007-2619

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-007-2619

#### **Thread Class:**

2a single mounting facility

#### Thread Length:

0.375 inches single mounting facility

#### **Overall Length:**

1.453 inches

#### **Overall Height:**

1.406 inches

#### **Overall Width:**

1.281 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.750 inches single actuator

#### **Nonturn Device Radius:**

#### 0.531 inches at 3: 00 o'clock

#### Individual Section Quantity:

1

Nonturn Device Type:

Pin at 3: 00 o'clock

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

3 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### Switch Actuator Positioning Increment:

36.0 degrees single actuator

#### **Detent Rotational Torque Range:**

+10.000/+18.000 inch-ounces single actuator

#### Switch Actuator Stop Device Type:

Fixed stop single actuator

### **Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

# NSN 5930-01-007-2619

Rotary Switch - Page 2 of 2

Style Designator:

Circular wafer, bushing mount

### Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A052b0

