

View Online at <https://aerobasegroup.com/nsn/5930-01-007-2624>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof and weatherproof

Body Diameter:

Between 0.720 inches and 0.780 inches

Bushing Length:

Between 1.260 inches and 1.320 inches

Body Length:

1.100 inches

Case Material:

Metal

Actuator Style:

Roller plunger

Actuator Free Position Height:

Between 1.750 inches and 1.800 inches

Actuator Roller Diameter:

0.375 inches

Actuator Roller Width:

0.120 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

F-14 tomcat aircraft.

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.125 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes lamp dc

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0