

View Online at <https://aerobasegroup.com/nsn/5930-01-007-2625>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Water resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.790 inches

Body Length:

0.438 inches

Body Width:

0.525 inches

Body Height:

1.550 inches

Unthreaded Mounting Hole Diameter:

0.150 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

0.400 inches

Actuator Roller Diameter:

0.255 inches

Actuator Roller Width:

0.062 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

16.0 ounces

Switch Actuating Force:

96.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.080 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes inductive ac and 2.000 amperes lamp ac

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0