

View Online at <https://aerobasegroup.com/nsn/5930-01-007-5721>

Hazardous Locations/environmental Protection:

Explosion proof

Individual Section Quantity:

2

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

3 each section front

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

500.0 ac at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0