

View Online at <https://aerobasegroup.com/nsn/5930-01-007-6079>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Bushing Length:**

Between 0.458 inches and 0.478 inches

**Body Length:**

0.562 inches

**Body Width:**

0.546 inches

**Body Height:**

0.562 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.237 inches and 0.246 inches

**Actuator Height:**

Between 0.655 inches and 0.719 inches

**Actuator Position-action Relationship:**

Center position maintained and down position momentary

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.701 inches

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0