

View Online at <https://aerobasegroup.com/nsn/5930-01-007-6503>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Bushing Length:**

0.578 inches

**Body Length:**

0.562 inches

**Body Width:**

0.546 inches

**Actuator Length:**

0.750 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.410 inches

**Actuator Width:**

0.380 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

Viking s-3a aircraft

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0