NSN 5930-01-007-6510



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-007-6510 **Body Style: Bushing mounted Bushing Length:** 0.620 inches **Body Length:** 0.900 inches **Body Width:** 0.656 inches **Body Height:** 1.475 inches **Actuator Length:** 0.730 inches **Actuator Style:** Rectangular **Actuator Height:** 0.628 inches **Actuator Width:** 0.730 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Uninclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac **Thread Series Designator:** Unef **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5930-01-007-6510

Push Switch - Page 2 of 2



Fiig:

A053a0