

View Online at <https://aerobasegroup.com/nsn/5930-01-008-2458>

**Inside Diameter:**

0.250 inches single connection

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

7.062 inches

**Overall Height:**

2.500 inches

**Overall Width:**

4.375 inches

**Mounting Slot Width:**

0.343 inches

**Body Length:**

5.250 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.874 inches

**Longest Vertical Distance Between Mounting Centers:**

5.875 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and slot

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

1800.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

500.0 milliamperes resistive load third voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+77.00/+1200.00 actuation point pounds per square inch and +50.00/+1173.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point screw

**Contact Voltage Rating In Volts:**

480.0 ac at sea level first voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0