

View Online at <https://aerobasegroup.com/nsn/5930-01-008-9415>

Hazardous Locations/environmental Protection:

Watertight

Actuator Style:

Roller plunger

Actuator Free Position Height:

2.200 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.185 inches

Housing Height:

1.745 inches

Housing Length:

3.894 inches

Housing Width:

1.620 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.344 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

Maximum Voltage Rating In Volts:

600.0 ac and 240.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

64.0 ounces

Actuator Movement:

Between 0.070 pretravel inches and 0.190 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 1.200 amperes resistive ac

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0