NSN 5930-01-009-0226

Thermostatic Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-009-0226

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.196 inches
Overall Height:
0.395 inches
Body Diameter:
0.630 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Clamp
Features Provided:
Tamper proof cap
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
Contact Load Current Rating: 7.2 amperes resistive load third voltage
7.2 amperes resistive load third voltage
7.2 amperes resistive load third voltage Contact Adjustability:
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 156.00 deactuation point degrees fahrenheit
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 156.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 156.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 277.0 ac at sea level third voltage
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 156.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 277.0 ac at sea level third voltage Media For Which Designed:
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 156.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 277.0 ac at sea level third voltage Media For Which Designed: Gas
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 156.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 277.0 ac at sea level third voltage Media For Which Designed: Gas Style Designator:
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 156.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 277.0 ac at sea level third voltage Media For Which Designed: Gas Style Designator: Disc
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 156.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 277.0 ac at sea level third voltage Media For Which Designed: Gas Style Designator: Disc Shelf Life:
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 156.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 277.0 ac at sea level third voltage Media For Which Designed: Gas Style Designator: Disc Shelf Life: N/a
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 156.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 277.0 ac at sea level third voltage Media For Which Designed: Gas Style Designator: Disc Shelf Life: N/a
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 156.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 277.0 ac at sea level third voltage Media For Which Designed: Gas Style Designator: Disc Shelf Life: N/a Unit Of Measure:
7.2 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 176.00 actuation point degrees fahrenheit and 156.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 277.0 ac at sea level third voltage Media For Which Designed: Gas Style Designator: Disc Shelf Life: N/a Unit Of Measure: Demilitarization: