NSN 5930-01-009-3615

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-009-3615

Thread Class: 3b single pressure connection **Thread Length:** 0.370 inches single pressure connection **Overall Length:** 3.340 inches **Body Diameter:** 1.380 inches **Body Length:** 2.260 inches **Overall Diameter:** 1.380 inches **End Application:** Ship, ohio class ssn (trident) **Pressure Switch Type:** Gage **Operating Tempurature Rating:** Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit **Mounting Method:** Input port Thready Qty Per Inch (tpi): 20 single pressure connection **Contact Action Stimulus:** Increase **Proof Pressure:** 1000.00 pounds per square inch gage **Thread Size:** 0.438 inches single pressure connection **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Sensing Element Burst Pressure:** 2500.00 pounds per square inch gage **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 5.0 amperes resistive load single voltage **Contact Adjustability:** Deactuation point adjustable and actuation point adjustable, preset **Contact Adjustment Range:**

+2.00/+10.00 actuation point pounds per square inch gage and +2.00/+10.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

NSN 5930-01-009-3615

Pressure Switch - Page 2 of 2



~	Calmandina	D -4!
Junaci	Stimulus	Raunu.

1.00 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at altitude single voltage

Pressure Connector Type:

Swivel nut, gasket seal, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0