## NSN 5930-01-009-5679

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-009-5679

**Thread Class:** 

2a single threaded bushing

**Overall Length:** 

Between 4.940 inches and 5.060 inches

**Body Length:** 

Between 3.660 inches and 3.720 inches

**Overall Diameter:** 

Between 0.614 inches and 0.625 inches

**End Application:** 

Radar system antps43e

**Tempurature Sensing Element Type:** 

Expanding shell

Width Across Flats:

1.125 inches

**Mounting Method:** 

Threaded bushing

Thready Qty Per Inch (tpi):

14 single threaded bushing

**Contact Action Stimulus:** 

Increase

Thread Size:

0.500 inches single threaded bushing

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Screw

**Contact Load Current Rating:** 

15.0 amperes resistive load single voltage

**Contact Adjustability:** 

Deactuation point not adjustable and actuation point adjustable, preset

**Contact Adjustment Range:** 

+25.00/+225.00 actuation point degrees fahrenheit

**Contact Adjustment Type:** 

External actuation point screw

**Contact Stimulus Rating:** 

149.00 actuation point degrees fahrenheit and 156.00 actuation point degrees fahrenheit and 147.00 deactuation point degrees fahrenheit and 154.00 deactuation point degrees fahrenheit and 2.00 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:** 

250.0 ac at sea level single voltage

**Special Features:** 

Weapon system essential

## NSN 5930-01-009-5679

Thermostatic Switch - Page 2 of 2



Frequency In Hertz:
60.0 single voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical
Thread Series Designator:
Npt single threaded bushing
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A048b0