

View Online at <https://aerobasegroup.com/nsn/5930-01-009-5686>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Hazardous Locations/environmental Protection:

Vibration proof

Overall Length:

Between 1.941 inches and 2.001 inches

Overall Height:

Between 1.720 inches and 1.780 inches

Overall Width:

Between 1.345 inches and 1.405 inches

First Flat Length:

0.403 inches single actuator and 0.409 inches single actuator

Flat Height:

0.198 inches single actuator and 0.201 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.809 inches single actuator and 0.815 inches single actuator

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 12: 00 o'clock

Switch Contact Basic Design:

Pile-up

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Cam actuated

Pile-up Contact Form Arrangement:

1z single switch single section in-line

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

277.0 highest ac voltage rating at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, slotted, flatted single actuator

Terminal Type:

Quick disconnect, male

Contact Switching Action:

Makes before breaks single section in-line

Contact Load Current Rating:

25.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

In-line, pile-up, panel mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0