NSN 5930-01-009-5690

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-009-5690

Hazardous Locations/environmental Protection: Explosion proof **Overall Length:** Between 4.510 inches and 4.750 inches **Overall Diameter:** 2.220 inches **Individual Section Quantity:** 1 **Operating Tempurature Range:** -65.0/+125.0 degrees celsius Switch Contact Basic Design: Nonpile-up symmetrical **Pole Quantity:** 1 single section front **Throw Quantity:** 4 single section rear **Features Provided:** Actuator knob and metallic inclosure **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Rotor Through Connection Quantity:** 1 single section Switch Actuator Indexing Position Quantity: 4 single actuator **Terminal Type:** Connector, receptacle **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 45.0 degrees single actuator **Detent Rotational Torque Range:** +1.000/+3.000 inch-pounds single actuator **Contact Load Current Rating:** 500.0 milliamperes resistive load dc at sea level **Special Features:** Case marked knob end 0 1 2 3 level sim tgt **Style Designator:** Tap, circular, bushing mount Shelf Life: N/a Unit Of Measure:

NSN 5930-01-009-5690

Rotary Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A052b0

