## NSN 5930-01-009-7612

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-009-7612 **Thread Class:** 2b single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 3.844 inches **Overall Height:** 4.125 inches **Overall Width:** 4.125 inches First Flat Length: 0.875 inches single actuator Flat Height: 0.250 inches single actuator **Shaft Diameter:** 0.375 inches single actuator **Shaft Length:** 1.250 inches single actuator **Individual Section Quantity: Knob Manufacturer Code:** 82121 **Longest Horizontal Distance Between Mounting Centers:** 2.281 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.281 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 3 each section rear **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 20 single mounting facility **Thread Size:** 0.250 inches single mounting facility

500.0 ac at sea level

**Contact Voltage Rating In Volts:** 

## NSN 5930-01-009-7612

Rotary Switch - Page 2 of 2



## **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round, flatted, threaded hole single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 90.0 degrees single actuator **Contact Load Current Rating:** 30.0 amperes resistive load ac at sea level **Style Designator:** Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No Fiig: A052b0