NSN 5930-01-010-7639

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-010-7639

Inside Diameter:

0.250 inches all connections

Overall Length:

4.300 inches

Overall Height:

2.620 inches

Overall Width:

2.620 inches

Body Length:

3.400 inches

Unthreaded Mounting Hole Diameter:

0.225 inches

Longest Horizontal Distance Between Mounting Centers:

2.125 inches

Longest Vertical Distance Between Mounting Centers:

2.125 inches

Pressure Switch Type:

Differential

Mounting Method:

Unthreaded hole

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

18 all pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

250.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

1.00 actuation point pounds per square inch and 90.00 actuation point pounds per square inch

NSN 5930-01-010-7639

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0